The Thermo Scientific Heraeus
Labofuge 300 is a small medical
centrifuge with swinging bucket
rotor, ideal for centrifugation of blood
collection tubes and medical
laboratories or practices with low
sample throughput.

Thermo Scientific Heraeus Labofuge 300


An economical and comprehensive small medical centrifuge with swinging bucket rotor


Benefits

- · Economical small centrifuge with swinging bucket rotor
- Ideal centrifugation of blood collection tubes
- Complete system with 8-place swinging bucket rotor and buckets
- Outstanding quality and reliability with induction drive and microprocessor control



Swinging Bucket Rotor





Blood Collection Tubes with Gel Barrier

- **A.** Using fixed angle rotors with gel barrier blood collection tubes can result in plasma contamination.
- **B.** The swinging bucket rotor purifies plasma with no red blood cell contamination.



Ideal for Virus Testing

The Thermo Scientific Heraeus Labofuge 300 is particularly suited to diagnostics and therapy of viral diseases (HIV, hepatitis).

In the field of virus testing, tubes with a gel barrier ("gel tubes") are commonly used. Immediately after a blood sample has been taken, these tubes must be spun.

Once centrifugation is complete, the blood plasma is separated from red blood cells by a layer of gel. This gel layer prevents mixing and resultant decomposition of viruses.

Unlike fixed angle rotors, which can lead to contamination within the gel tube, the Heraeus® Labofuge® 300's swinging bucket rotor ensures the gel barrier sticks to the tube wall with no traces of contamination in the plasma. The tubes can then be stored or transported to a laboratory for virus testing.

The Heraeus Labofuge 300 can also spin ordinary blood sample tubes and glass tubes.



www.supplylab.pt

geral@supplylab.pt

Cacém Park - Edifício 9 Estrada de Paço de Arcos nº88 2739-512 Agualva Cacém T +(351) 21 4278700 F +(351) 21 4278709



Thermo Scientific Heraeus Labofuge 300 Centrifuge



Specifications		
Drive	_	Induction drive without carbon brushes
Control		Microprocessor control through Easycontrol I with variable pre-selection and
		display of speed and time, Quick-run
Max. speed	rpm	4000, adjustable in increments of 10
Min. speed	rpm	300
Max. RCF	x g	2028
Temperature range	°C	-
Noise level at max. speed	dB	< 60
Run time	min	0–99, cont. operation
Program memory		The most recent data remains in the memory
Construction		Galvanized steel chassis with armored chamber and plastic outer casing
Centrifuge protection		Lid lock and interlock
Dimensions (H x W x D)	mm (inch)	315 x 380 x 475 (12.4 x 15 x 18.7)
Weight	kg (lb)	30 (66)
Power consumption	W	180
Test standards		Manufactured and tested in accordance with EN 61 010-1,
		EN 61 010-2-020, EN 50 081-1,
		EN 50 082-1; UVV VBG 7z test is not required, CE, CSA (120V only)

Rotor Specification	ıs	Swinging Bucket	35° Fixed Angle	
Cat. No		76003265* ⁺	75003760 [†]	
Max. speed	rpm	3600	4000	
Max. RCF	хg	2028	1915	
Max. capacity	mL	8 x 15	12 x 15	
Braking/accel. curves	sec	28/29	30/32	
Min./max. radius	mm (inch)	57/140 (2.2/5.5)	51/107 (2.0/4.2)	

^{*} Included with Labofuge 300

† Complete with all adapters necessary

Accessories					
	Max. tube size diam. x length mm (inch)	Tubes per rotor	Color buckets	Cat No.	
Accessories 76003265:					
15 mL bucket	16.5 (0.7) x 113 (4.5)	8	red	76003262	
7 mL bucket	13 (0.5) x 113 (4.5)	8	yellow	76003263	
5 mL pad	NA x 90 (3.5)	_	_	76003266	
Accessories 75003760:					
5 mL adapter	13 (0.5) x 75 (2.95)	12	tan	76003226	
7 mL adapter	13 (0.5) x 113 (4.5)	12	yellow	76003225	
10 mL pad	16.5 (0.7) x 117 (4.6)	6	<u>-</u>	75003762	
Protective sleeves for glass	16 (0.6) x 100 (3.9)	12	_	75003763	

Ordering Information Description	Cat. No.
Heraeus Labofuge 300 with 8 x 15 mL swinging bucket rotor	75003231
8 buckets each for 7 mL and 15 mL and distance pads, 120V / 60Hz	
Heraeus Labofuge 300 with 8 x 15 mL swinging bucket rotor	75003230
8 buckets each for 7 mL and 15 mL and distance pads, 230V / 50-60Hz	

^{© 2008} Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.





www.thermo.com/centrifuge

North America: USA/Canada +1 866 984 3766

Europe: Austria +431 801 40 0, Belgium +32 2 482 30 30, France +33 2 2803 2000, Germany national toll free 08001-536 376, Germany international +49 6184 90 6940, Italy +39 02 02 95059 434-254, Netherlands +31 76 571 4440, Nordic countries +358 9 329 100, Russia/CIS +7 (812) 703 42 15, Spain/Portugal +34 93 223 09 18, Switzerland +41 44 454 12 12, UK/Ireland +44 870 609 9203

Asia: China +86 21 6865 4588 or +86 10 8419 3588, India +91 22 6716 2200, Japan +81 45 453 9220, Other Asian countries +852 2885 4613

Countries not listed: +49 6184 90 6940 or +33 2 2803 2000

