



## ROTOR SPECIFICATIONS

<b>Type</b>	Fixed Angle
<b>Material</b>	Titanium
<b>Capacity</b>	8 x 5.0 mL
<b>Maximum Speed</b>	110,000 rpm
<b>Tube Dimensions Ø x L</b>	13 x 63 mm
<b>Angle</b>	30°
<b>K Factor</b>	15.4
<b>Net Weight</b>	1.07 kg /2.4 lbs
<b>Warranty</b>	5 years

	<b>RCF</b>	<b>RADIUS</b>
<b>Maximum</b>	690,652 xg	51.1 mm
<b>Average</b>	510,893 xg	37.8 mm
<b>Minimum</b>	331,135 xg	24.5 mm

## ROTOR AND ACCESSORIES ORDERING INFORMATION

## S110-AT Rotor Package includes:

<b>Description</b>	<b>Cat. No.</b>
S110-AT Rotor <sup>1</sup>	45539
4.0 mL PC Thick-Walled Tubes (qty. 2 pkg. of 50)	45239
Large O-ring for Cover (qty. 2)	45703
Small O-ring for Cover (qty. 2)	45294
Rotor Holding Fixture	45266
Lubricant	61556
Vacuum Grease	65937
Instruction Manual	45735

## Accessories:

<b>Description</b>	<b>Cat. No.</b>
Starter Kit for use with 13 mm Re-Seal Tubes {Includes 1 Crown (45321), 10 Plugs (45307), Wrench (45308) and Removal Tool (45309)}	45320
13 mm x 51 mm Tube Vise	45534
Rotor Stand	45357
Cover Opener	45173

<sup>1</sup> Rotor compatible only with Thermo Scientific Sorvall MTX-150 and MX Series micro-ultracentrifuges.

## LABWARE ORDERING INFORMATION

Tube Vol. (mL)	Vol. Fill (mL)	Description	Cat. No.	Qty. /Pkg.	Tubes /Rotor	Max. Speed (rpm)	Max. RCF (xg)	Dims ØxL (mm)	REQUIRED TUBE CLOSURES, ADAPTERS, TOOLS & ACCESSORIES			
									Type	Cat. No.	Qty. /Pkg.	Description
5.0	5.1	PA Re-Seal Tube	45248	50	8	110,000	690,652	13 x 51	Closure	45321	1	13 mm Al Crown <sup>2</sup>
									Closure	45307	10	Stainless Steel Plug Wrench
									Tool	45308	1	Tube Removal Tool
									Tool	45309	1	Tube Vise
									Tool	45534	1	Tube Vise
5.0	5.0	PA Easy-Seal Tube	75000508	50	8	80,000	365,304	13 x 51	Closure	75000511	1	13 mm Al Crown <sup>2</sup>
									Tool	75000505	1	Crown Clamp
									Tool	75000506	1	Hex Driver
									Tool	75000507	1	Tube Removal Tool
									Tool	75000481	1	Easy-Seal Tube Vise
4.0	3.4	PC Thick-Walled Tube	45239	50	8	110,000	690,652	13 x 63	—	—	—	—
3.5	3.5	PA Easy-Seal Tube	75000509	50	8	80,000	365,304	13 x 45	Closure	75000511	1	13 mm Al Crown <sup>2</sup>
									Tool	75000505	1	Crown Clamp
									Tool	75000506	1	Hex Driver
									Tool	75000507	1	Tube Removal Tool
									Tool	75000481	1	Easy-Seal Tube Vise
3.5	3.5	PET Easy-Seal Tube	75000510	50	8	80,000	365,304	13 x 45	Closure	75000511	1	13 mm Al Crown <sup>2</sup>
									Tool	75000505	1	Crown Clamp
									Tool	75000506	1	Hex Driver
									Tool	75000507	1	Tube Removal Tool
									Tool	75000481	1	Easy-Seal Tube Vise
1.5	1.5	PA Easy-Seal Tube	75000512	50	8	80,000	365,304	13 x 29	Closure	75000511	1	13 mm Al Crown <sup>2</sup>
									Tool	75000505	1	Crown Clamp
									Tool	75000506	1	Hex Driver
									Tool	75000507	1	Tube Removal Tool
									Tool	75000481	1	Easy-Seal Tube Vise
1.5	1.5	High Performance Microtube	314352H01	100	8	55,000	172,663	11 x 42	Adapter	45587	1	Adapter for Microtube
1.5	—	Corning® Screw Cap Microtube <sup>3</sup>	—	—	8	110,000	582,000	—	Adapter	S412067	1	Adapter for Microtube

<sup>2</sup> Must order one crown for each place in the rotor.<sup>3</sup> Tubes must be purchased from manufacturer (cat. no. 430909).

© 2010 Thermo Fisher Scientific Inc. All rights reserved. Corning is a registered trademark of Corning Inc. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

For more information, please visit  
[www.thermoscientific.com/rotors](http://www.thermoscientific.com/rotors).

**Thermo**  
 SCIENTIFIC

LAB  
 www.supplylab.pt