

# G100 CO2 INCUBATOR ANALYSER







# ACCURATE INCUBATOR VERIFICATION TOOL

## G100

New CO<sub>2</sub> analyser specifically designed to monitor CO<sub>2</sub> for the verification of incubators in research and pharmaceutical markets. This unit has been developed to incorporate the latest technology and specification requirements, that provide the user with a fast, simple to use and accurate piece of laboratory kit.

#### **Benefits**

- Improved accuracy on CO<sub>2</sub> readings
- Quick verification of CO<sub>2</sub> incubator levels
- · Time saving with dual temperature probes
- Large data storage and user friendly software and download
- · Easy to read large well lit display
- Built in gas moisture removal

#### **Features**

- CO<sub>2</sub> 0 20%
- Options for:
  - O<sub>2</sub> 0-100%
  - Dual temperature probes 0 50°C
  - Data storage and download
  - Humidity Sensor 0-100%

#### **Applications**

- IVF
- Research
- Laboratories
- Medical



## **Product Specifications**

G100		
GAS RANGES		
Gases Measured		
Cases incasured	CO <sub>2</sub>	By custom dual wavelength infra-red cell reference channel
	O <sub>2</sub> (Optional)	By internal electrochemical cell
Oxygen cell lifetime	Approximately 3 years in air	
Range	CO <sub>2</sub> O <sub>2</sub>	0-20% 0-100%
	Gas	
Measurement Accuracy	co <sub>2</sub>	Accuracy ± (1% range +2% of reading) at reference conditions Temperature dependence ± 0.2% reading °C (typical at 5% CO2) Pressure dependence ± 0.02% of reading/hPa (typical at 5% CO2)
	02	±1.0% Full Scale @ constant temperature and pressure ± 2.0% Full Scale over operating temperature range
Response time T <sup>90</sup>	CO <sub>2</sub> O <sub>2</sub>	≤20 seconds ≤60 seconds
FACILITIES		
Temperature ( Optional)	x2 using optional probes 0 °C to +50 °C	
Temperature accuracy, typical	± 0.2 °C over the range (± 0.1 °C between 32-44 °C)	
Barometric pressure	800-1200 mbar	
RH measurement (Optional)	RH Probe 0-100% RH non condensing	
RH accuracy	+/- 1.5% RH across the range	
Visual and audible alarm	User selectable CO <sub>2</sub> and O <sub>2</sub> alarm levels	
Communications	USB type B mini-connector, HID device class	
Data Storage	1000 readings	
ENRIONMENTAL CONDITIONS		
Operating temperature range	5 °C - 40 °C	
Relative humidity	0-95% non condensing (RH Probe 0-100% non condensing)	
Barometric pressure	± 200 mbar from calibration pressure	
PHYSICAL		
Weight	495 grams	
Size	L 165mm, W 100mm, D 55 mm	



